

EASY F

INTANK VERTICAL PUMPS

Intank cartridges filter system

EASY F - Inlet cartridge filter units filter element is placed directly on suction pump

They have to be place inside process tank.

Features:

- Dry run capability
- No leakages outside of process tank della vasca di lavoro
- Easy set up .
Any piping to connect at filter unit.
Only electrical connection.
- Easy maintenance:
Fast filter element replacemnet

Capacity:

à Filter units EASY F are made in PP or PVDF,
Istandard version are made with:
one cartridge 10" o 20"
for cartridegs 10" o 20"
Flow rate from 1000 to 5000 l/h



EASY F

Model EASY F	1500/N	2000/N	4000/N	5000/N
Flowrate l/h	1500	2000	4000	5000
Cartridges (n°x l")	1 x 10"	1 x 20"	4 x 10"	4 x 20"
Surface Area. m²	0,30	0,60	1,25	2,50
Power KW	0,13	0,13	0,26	0,26
Suction ø mm	25	25	30	30
Discharge ø mm	20	20	25	25
Weigt kg	5	5,5	10	11
pump depth mm	250	250	300	300
filter depth mm	530	780	570	820

Other:

- Suitable for Eductor application
- Materials: Polipropilene PP (up 70°C)
- Materials: Polypropilene PP (up 70° C)
PVDF (up 95° C)
- Wound depth, carbon & melt blwn cartrdige
- Customized version
-



la fonte s.r.l.

Via Careno, 5 - 21040 Veduggio Olona (Va) Italy

Tel. +39 0332 402168 - Fax +39 0332 402169

e-mail: info@lafontesrl.it - www.lafontesrl.it

la fonte
srl.it