

BAG

FILTER UNITS



Bag filter units are usually used for filtration of corrosive solution.

Excellent chemical resistance, rugged construction and easy maintenance make them ideal alternative at discs and cartridges filter systems.

Filter units with bag are normally made with:

- Magnetic drive pump (capacity 3 ÷ 20 m³/h)
- PP base
- PP monoblocc filterchamber
- Filterbag (capacity 2,5 - 7,9 - 17,3 l)
- Temperature exercise max 75°C
- PVDF version is also available for application up to 95 °C

The yare available in special version according with customer need.

BAG FILTER UNIT					
Mod.	Pump	Motor KW	Q max l/min	Filter BAG Capacity (l)	Inlet/Outlet (mm)
BFP 10/40 MPP051	MPP051	0,11	50	2,5	25/20
BFP 10/40 MPP101	MPP101	0,25	100	2,5	32/32
BFP 18/40 MPP101	MPP101	0,25	100	7,9	32/32
BFP 18/40 MPP201	MPP201	0,55	200	7,9	40/32
BFP 18/80 MPP201	MPP201	0,55	200	17,3	40/32
BFP 18/80 MPP251	MPP201	1,1	240	17,3	50/40
BFP 18/80MPP302	MPP302	1,5	300	17,3	50/40



Please contact us for additional technical details.

la fonte s.r.l.

P.le Cocchi, 6 - 21040 Veduggio Olona (Va) Italy
 Tel. +39 0332 402168 - Fax +39 0332 402169
 e-mail: info@lafontesrl.it - www.lafontesrl.it

la fonte
srl.it